





COASTAL SERIES

It's two windows with one continuous head and sill.

Currently the "Twin" has been tested up to a double 26 or DLO size (72 %" x 70 ¾"), with a 67.5 dp.

The benefits of installing this window are many, including:

- · Less time to install (You're installing 1 window instead of 2 windows and a mull bar)
- Less chance of water intrusion at the mull bar application
- · Fewer windows to unload or transport to job site
- Less complicated installation
- · Less chance of failed mull



inspection with factory "Twin" Side-by-Side Window Impact or Non-Impact

Certified To Meet or Exceed Expectations

All CWS PVC windows are AÂMA and NFRC certified, and are compliant with ENERGY STAR® and Green Building standards.

Wind-Pact Plus Large Missile Impact Windows

- Provide a greater level of safety and security
- Reduce danger of flying or falling glass
- Resist forced entry
- Dampen unwanted outside sounds
 SH up to 100DP, HS up to +60/-75DP, Casement up to 67.5DP, Awning up to 67.5DP, Patio Doors up to 60DP
- Tested to Miami-Dade County, Florida and ASTM specifications for impact
- Available with energy efficient LoĒ² & LoĒ³ Glass
- NOW OFFERING Cardinal NEAT® AND LoĒ-i81

Advantages of Cardinal LoĒ³

For the advantages of laminated glass with a reduced solar heat gain, Cardinal offers LoE³ Coatings. Though virtually

invisible to the eye, Cardinal's patented LoE³ coating reduces solar gains, thus reducing air conditioning costs.

Neutral in color, the microscopically thin LoĒ³ coating in laminated glass has high visible light transmission and low outdoor and indoor reflectivity. LoĒ³ Coating Glass Airspace Glass



If the building envelope is breached through a broken window, wind may enter the building causing an increase in pressure that could lift the roof and push the walls outward.

Laminated glass helps to preserve the building envelope, keeping wind and other elements outside.





CWS vinyl windows are available in three easy-to-clean colors: white, adobe, and two-tone bronze.



Watch Out for Impostors

CWS uses color-stabilized vinyl to prevent discoloration and keep your windows looking new. Vinyl windows of lesser quality may start out white but can end up looking dingy and discolored after normal exposure to the elements.



Advanced Design and Engineering

- Multiple hollow chambers for strength and insulation.
 Dual-pane insulated glass with double-strength glass (standard).
- 3) Extruded Florida flange on all frame types.4) Thick vinyl walls for added structural integrity.
- 5) Covered weep holes in sill control water penetration and drainage.



1900 SW 44th Avenue Ocala, Florida 34474 WWW.CWS.CC

SINGLE HUNG / HORIZONTAL SLIDER

Externally glazed operating sash and frame for better air and water performance

Sealed multi-hollow extrusion for strength and energy efficiency

Weather stripped interlock with dual seal sash to frame, creates a positive seal keeping out harsh elements

> Exterior beveled frame for architectural style

Extruded Florida flange on all frame types

Heavy duty 3" frame thickness

White Interior

Welded frame and sash corners for strength and water tightness

%" overall insulated glass for UV and heat gain thermal protection

Double action self-locking sash locks for added security

Continuous integral lift-handle on top and bottom rails for finger-tip ease of operation

PVC extrusions are impact and corrosion resistant

Your Authorized Custom Window Systems Dealer: